

THE 603GC



CONCRETE. STONE. MASONRY. **UNSTOPPABLE**



603GC

PORTABLE AND AFFORDABLE VERSATILITY

The 603GC is designed to be an affordable, light-duty workhorse. The sturdy 64 cc engine, with its advanced rear-ported, multi-chamber air filtration cranks out more than enough power to make plunge cuts up to 10 inches (25 cm) deep. An expert tool at an entry level price and weighing in at less than 18 lbs (8 kg), the 603GC is a handy member of any crew.

603GC PRODUCT SPECIFICATIONS	
WEIGHT	17.6 lbs (8.0 kg) with bar and chain
BAR LENGTH	10 in (25 cm)
ENGINE SPEED	11500 +/- 500 rpm, 2800-3200 rpm idle
HORSEPOWER	4.2 hp (3.1 kW) @ 9500 rpm
ENGINE TYPE	2-stroke, single cylinder, air cooled
DISPLACEMENT	3.9 cu in (64 cc)
CHAIN SPEED	5100 fpm (25.9 m/s), free running
POWERHEAD DIMENSIONS	17 in (44 cm) length 10 in (25.5 cm) height 11.6 in (29.5 cm) width
NOISE LEVEL	101 dB @ 3 ft (1 m)
VIBRATION LEVEL	10.1 meters/second ² (front handle)
WATER SUPPLY	Minimum 20 psi (1.5 bar)
FUEL MIX RATIO	25:1 (4%) fuel-to-oil
FUEL CAPACITY	0.26 gallons (1 liter), 12-15 minutes run time per tank

SAW SELECTION

In addition to cutting depth and power requirements, estimated frequency of use is important when selecting a saw. Use the chart below to determine the right saw for your cutting needs.

