THE 680GC



CONCRETE, STONE, MASONRY, UNSTOPPABLE



A WHOLE DIFFERENT ANIMAL

The 680GC is the much anticipated revolution in concrete chain saws. Built to be the most reliable gas saw ICS® has ever produced, it's packed with innovations. The distinctive black powerhead houses redesigned carburetion and ignition systems that work together to ensure easy starting, cooler operation, and dependable performance at just about any elevation. Improved airflow design keeps the engine much cooler, extending its life. Available with 12 in (30 cm) and 14 inches (35 cm) guidebars and the entire line of TwinMAX™ diamond chain.

	_		_	
frequency of	use is in	nportant when	er requiremen selecting a sav saw for your cu	w. Use the
	DAILY	WEEKLY	MONTHLY	QUARTERLY
603GC	· ——	_		
680GC	:			
633GC	· ——			
814PR0				
880F4/853PRO				

680GC PRODUCT SPECIFICATIONS			
WEIGHT	21 lbs (9.5 kg) with bar and chain		
BAR LENGTH	Up to 14 in (35 cm)		
ENGINE SPEED	11500 +/- 500 rpm, 2800-3200 rpm idle		
HORSEPOWER	5.7 hp (4.2 kW) @ 9000 rpm		
ENGINE TYPE	2-stroke, single cylinder, air cooled		
DISPLACEMENT	4.9 cu in (80 cc)		
CHAIN SPEED	5300 fpm (27 m/s), free running		
POWERHEAD	18 in (45 cm) length		
DIMENSIONS	11.5 in (29 cm) height		
	10 in (25 cm) width		
NOISE LEVEL	100 dB @ 3 ft (1 m)		
VIBRATION LEVEL	10.5 meters/second² (front handle)		
WATER SUPPLY	Minimum 20 psi (1.5 bar)		
FUEL MIX RATIO	25:1 (4%) fuel-to-oil		
FUEL CAPACITY	0.23 gal (.88 liter), 15-18 minutes		
	run time per tank		

