


# 307

## Utility Grade Duct Tape



<b>Backing:</b>	PE Coated Cloth
<b>Adhesive:</b>	Rubber
<b>Liner:</b>	N/A
<b>Colors:</b>	Silver, Black
<b>Specifications:</b>	Tested in accordance with UL 723
<b>Standard Sizes:</b>	48mm x 55m, 72mm x 55m

### Applications

- Maintenance & general repair
- Bundling, patching & mending
- Joint sealing & pipe wrapping
- Heavy-duty box sealing

### Features

- PE-Coated Cloth Backing
- Natural rubber based adhesive
- Low VOC Content

### Benefits

- Conformable & hand tearable
- Resists Twisting & curling
- Bonds well to most surfaces, good all climate performance
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

### Physical Properties

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	7 mils	177.8 mic	ASTM D-1000
<b>Adhesion to Steel</b>	46 oz/in	5.03 N/cm	PSTC-101
<b>Tensile Strength</b>	21 lb/in	36.78 N/cm	ASTM D-1000
<b>Operating Temperature</b>	40-200°F	4-93°C	
<b>VOC Content</b>	<1 g/L		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F  
Standard Shelf Life (at 25C): 24 months from date of manufacture.