

# NORTHTOWN

Pipe Protection Products

Product Data Sheet

## **POLYWRAP 3' X 100' FLAT SHEETING POLYETHYLENE PROTECTION FOR CAST IRON, DUCTILE IRON AND STEEL**

**FOR WRAPPING FITTINGS AND APPURTENANCES  
AND FOR USE IN JOINT MAKE-UP, AS DESCRIBED IN 4.4.2.2 OF THE AWWA  
STANDARD**

### **SPECIFICATIONS**

The domestic 8 mil minimum, group 2, linear low density, flat tube, virgin polyethylene film provided meets or exceeds the requirements of AWWA C105-10, ANSI A21.5-10, ASTM D4976 and NT4112-10. The film is marked showing trademark, year of manufacture, type of resin, specification conformance and words "Warning Corrosion Protection-Repair Any Damage"

### **PROPERTIES**

Tensile Strength	3600 psi, minimum-ASTM D882
Elongation	800%, minimum-ASTM D882
Dielectric Strength	800V/mil, minimum-ASTM D149
Impact Resistance	600 g, minimum-ASTM D1709-B
Propagation Tear Resistance	2550 gf, minimum-ASTM D1922

**800 WRAP-A-PIPE**  
**P.O. Box 2064 Huntington Beach CA 92647**  
**714 897-0700 Fax 714 897-0600**