

NORTHTOWN

PIPE PROTECTION PRODUCTS

POLYWRAP

3' X 100'

FLAT SHEETING

POLYETHYLENE PROTECTION FOR CAST IRON, DUCTILE IRON AND STEEL

FOR WRAPPING FITTINGS AND APPURTENANCES
AND FOR USE IN JOINT MAKE-UP, AS DESCRIBED IN 4.4.2.2 OF THE AWWA
STANDARD

SPECIFICATIONS

The domestic 8 mil minimum, group 2, linear low density, flat tube, virgin polyethylene film provided meets or exceeds the requirements of AWWA C105-05, ANSI A21.5-05, ASTM D4976 and NT4112-05. The film is marked showing trademark, year of manufacture, type of resin, specification conformance and words "Warning Corrosion Protection-Repair Any Damage"

PROPERTIES

Tensile Strength	3600 psi, minimum-ASTM D882
Elongation	800%, minimum-ASTM D882
Dielectric Strength	800V/mil, minimum-ASTM D149
Impact Resistance	600 g, minimum-ASTM D1709-B
Propagation Tear Resistance	2550 gf, minimum-ASTM D1922

P.O. BO 2064 HUNTINGTON BEACH, CA 92647
(714) 897-0700 FAX (714) 897-0600