

# NORTHTOWN

**Pipe Protection Products**

**Product Data Sheet**



## **POLYWRAP - C**

### **DESCRIPTION**

Polywrap – C is a proven, effective and cost efficient method for the protection of smaller piping to be directly buried underground or to be encased in concrete. It is flexible and will conform to the pipe when backfilled.

### **INSTALLATION**

Cut a desired length of Polywrap – C, slip it over the pipe pulling it over the barrel length. Joints in the polywrap should be overlapped a minimum of six inches. Repair any damage to the polywrap with tape or a short length of polywrap cut and wrapped around the pipe and secured in place.

### **SPECIFICATIONS**

The polyethylene sleeve shall be manufactured of virgin material conforming to the following specification and listed in ASTM D-1248:

Tensile Strength	MD-3400 psi	TD-2800 psi
Density	924	
Elongation	MD-300% TD-500%	
Thickness	0.006" (6mil) tolerance not to exceed 10%	
Colors	Natural, Blue, Orange and custom	

### **DISTRIBUTION**

Natural (clear) or colored polyethylene tubing is available in several widths suitable for all sizes of pipe. Availability, pricing, and other information can be secured by contacting our sales office.

**800 WRAP-A-PIPE**

**P.O. Box 2064 Huntington Beach CA 92647**

**714 897-0700 Fax 714 897-0600**