

Pipe Protection Products

POLYWRAP

3'X100'

FLAT SHETING

POLYETHYLENE PROTECTION FOR CAST IRON,
DUCTILE IRON AND STEEL

FOR WRAPPING FITTINGS AND APPURTENANCES
AND FOR USE IN JOINT MAKE-UP, AS DESCRIBED IN 4.4.2.2 OF THE
AWWA STANDARD

SPECIFICATIONS

The domestic 8 mil. minimum, group 2, linear low density, flat or folded sheet, virgin polyethylene film provided meets or exceeds the requirements of AWWA C105-10, ANSI A21.5-10, ASTM D4976 and NT4112-10. The film is marked showing trademark, year of manufacture, type of resin, specification conformance and words "Warning Corrosion Protection-Repair Any Damage"

PROPERTIES

Tensile Strength	3600 psi, minimum-ASTM D882
Elongation	800%, minimum-ASTM D882
Dielectric Strength	80V/mil, minimum-ASTM D149
Impact Resistance	60 g, minimum-ASTM D1709-B
Propagation Tear Resistance	2550 gf, minimum-ASTM D1922

800 WRAP-A-PIPE

P.O. Box 2064 Huntington Beach CA 92647

714 897-0700 Fax 714 897-0600