

Pipe Protection Products

HMWPE Cathodic Protection Cable 600v

Stranded

Application

Direct earth burial for cathodic protection of metallic structures.

Cathodic Protection Cable is used in systems that protect metallic structures from electrolysis and corrosion. The product acts as a DC feeder cable to drain static electricity, providing cathodic protection for: Pipelines, well Casings, storage tanks, water towers, marine craft, bridges, piers/pilings, railroad.

Description

Multi conductor, stranded, low density, high molecular weight polyethylene insulation.

Specifications

Designed and approved for direct earth burial, Northtown Cathodic Protection Cable is available from 12 gauge through 1 gauge. Standard black insulation consists of low density, high molecular weight polyethylene (HMWPE) which offers excellent resistance to abrasion and corrosion from chemicals, salt and water. The material has high dielectric strength and remains flexible at low temperatures. All sizes meet or exceed ASTM standards B-8 & B-3 , D-1248, Type I , Class C , Category 5 , Grade E-4 & E-5. Icea S61-402, Part 6, paragraph 6.11.4.

HMWPE COPPER					
Gauge	Number Of Strands	Insulation Thickness	NOM. OD	STD. Package*	Shipping Weight LBS
12	7	0.110"	0.309"	500'	24
10	7	0.110"	0.316"	500'	30
8	7	0.110"	0.368"	500'	57
6	7	0.110"	0.398"	500'	62
4	7	0.110"	0.445"	500'	91
2	7	0.110"	0.512"	500'	131
1	19	0.125"	0.584"	500'	172

* Larger length spools available upon request

800 WRAP-A-PIPE

P.O. BOX 2064 Huntington Beach, CA 92647

(714) 897-0700 Fax (714) 897-0600